Supplementary Preliminary Amendment Application S/N 10/634,406

Docket Nr. PDS-003C2 Page 2 of 8

In the claims:

Claims 1 - 129: (Cancelled)

130. (Currently Amended) A computer for use in a local area network the computer

comprising:

a memory located within the computer;

a non-essential circuitry located within the computer;

a first internal power supply <u>located within the computer and arranged to supply power to</u>

said memory and said non-essential circuitry, said first internal power supply being fed power

from an electrical mains;

a second internal power supply located within the computer and arranged to power said

memory, said second internal power supply being fed a limited power insufficient to power both

said memory and said non-essential circuitry, said limited power received via communication

cabling from an external power source, said communication cabling comprising pairs of twisted

copper wires at least one of which is arranged to transmit both said received limited power and

data for the computer; and

a controller receiving a control input from said first internal power supply indicative of

said mains fed power availability,

said controller being operative operative, responsive to said control input indicating that

said mains fed power of said first internal power supply is not available available, to supply

power to said memory from said second internal power supply, said non-essential circuitry not

being powered by said second internal power supply.

131. (Cancelled)

132. (Cancelled)

2

Supplementary Preliminary Amendment Application S/N 10/634,406 Docket Nr. PDS-003C2 Page 3 of 8

133. (New) A method of supplying back up power to a memory of a computer, the computer comprising the memory, a non-essential circuitry, a mains fed power supply and a secondary power supply, the method comprising:

feeding the secondary limited power supply a limited power insufficient to power both the memory and the non-essential circuitry, said limited power being fed via communication cabling from an external power source, said communication cabling comprising pairs of twisted copper wires at least one of which is arranged to transmit both said received limited power and data for the computer;

providing power to the memory and the non-essential circuitry from the mains fed power supply of the computer;

monitoring the availability of said power from the mains fed power supply; and

powering, in the event said power from said mains fed power supply is not available, said memory from said limited power fed secondary power supply, said non-essential circuitry not being powered by said second internal power supply.